



## Our Global Footprint

Janatics exports to over 46 countries in North America, Europe, Australia, Middle East, Africa and South East Asia.

The dedicated Janatics pre-sales and post-sales support team serve customers in USA, Vietnam, Indonesia and Middle East with sufficient inventory.



Marketed by:

**JANATICS GLOBAL SOLUTIONS PRIVATE LIMITED**

Rathinam Circle View, 4th Floor, B4 & C4, Race Course Road, Coimbatore - 641018, Tamil Nadu, INDIA.

P: +91 422 2678500 E: globaloffice@janatics.co.in

**Marketing offices:** Ahmedabad | Bengaluru | Chennai | Coimbatore | Hyderabad | Indore | Kolkata | Mumbai | New Delhi | Pune  
Rudrapur | Jaipur | Ludhiana | Sonipat | Bhiwadi | Nashik | Chandigarh | Kolhapur | Mysuru | Tiruppur | Nagpur



The future is here,

## TM AI COBOT


Native AI engine + Robotic arm + Vision system

All in **ONE**

## What Is An AI Cobot?

**AI Cobot** is a collaborative robot that seamlessly blends three technological domains together - AI, Vision, and Cobot. This integration effectively combines the functions of a 'brain,' 'eyes,' and 'hands,' enabling the cobot to perform visual tasks, making judgments, and executing actions much like a human. Automating processes not only saves time and resources but also promotes effective human-robot collaboration, enhancing overall production quality, and adds a significant value to your factory.


Fifteen years ago, collaborative robots introduced the concept of humans and robots working together. Today, the new generation of AI collaborative robots has turned the dream of having intelligent and reliable partners into a reality.



## Industry Applications

TM AI Cobot offers exceptional performance and compatibility. Equipped with a built-in vision system, it enables the robot to perceive its surroundings. Its AI brain also translates image data into precise commands for tasks such as positioning and detection, seamlessly integrating with the robot arm to execute tasks efficiently.

In the era of AI, TM AI Cobot is the best choice to for realizing smart factories.



# Introducing TM AI Cobot

The only AI-powered collaborative robot with advanced vision capabilities

# JANATICS

## TM AI Cobot

### TM AI Cobot S Series



### TM AI Cobot Series



### + Additional Types

#### TM Mobile Series

TM Mobile Series cobots can be integrated with almost all AGV/AMR brands on the market. With its embedded vision and TM Landmark vision function, the mobile series is extremely suitable for applications and tasks that require mobility. Such as machine tending or palletizing.

#### No Built-in Vision Robot Series

TM Robot Series offers robot arms with no built-in vision for users who want to integrate external cameras by themselves. Feel free to check on the pre-verified list of cameras from our TM Plug&Play™ series to save time on finding a compatible camera.

\*Under the palletizing scenario

# Introducing TM AI Cobot


The only AI-powered collaborative robot with advanced vision capabilities


# JANATICS

## SMART

### A perfect integration of cobot and machine vision


- Hand and eye integration for time/labor-saving solution
- Powerful vision function: The combination of traditional machine vision and AI vision offers the user a comprehensive vision function including vision positioning, measurement, defect inspection, OCR and barcode reading
- Easily manage both robot arm and vision functions within a single software, eliminating the need to learn two separate programs and concerns about system compatibility or interface issues



	TM built-in vision 	Robot arm + External vision
<b>Camera</b>	All-in-one	Requires additional mechanism for integration
<b>Camera signal cable and power cord</b>	Internally routed cables	Externally routed cables can lead to problems like tangled or pulled cables or dust resulted from friction
<b>Vision recognition system</b>	5M color camera, auto focus, built-in light source, various applications	Complicated configuration of lens, camera, light source and software
<b>Vision and Robot Programming</b>	Integrated in one software TMflow™ for easy programming	Need to handle the communication interface of 2 different software
<b>Charge</b>	The cost of the robot arm includes the vision system	Additional charge of vision software /hardware is required

### A plug-and-play 3D vision solution requires no additional software/hardware integration

When incoming materials are stacked or arranged in different configurations, the positioning function may become ineffective or less accurate due to the limitations of a standard robot's 2D vision, which cannot capture 3D coordinates. To overcome this challenge, Techman Robot has introduced TM 3D Vision™, a 3D machine vision solution with paired designated Plug&Play 3D camera, designed to expand the range of items recognizable by the vision system and enhance the precision of both vision-based positioning and arm movement.



#### Traditional Solution


Requires more time and labor costs to integrate robot arm, 3D camera, and software from different brands

#### All-In-one Solution

Significantly reduces integration costs and efforts, maintenance and accountability issues

### Features

- The integration of 3D software and TMflow™ interface achieves high integration and easy operation
- No additional vision controller is required. No need for complicated system handshaking settings
- Can be used with the collision check function and prevent any potential collision risks. This is highly recommended for the Random Bin Picking applications.



▪ Picking up scattered materials

▪ Single item 3D positioning

# Introducing TM AI Cobot

The only AI-powered collaborative robot with advanced vision capabilities


# JANATICS

## SIMPLE


### More Freedom to Program the Cobot

TMflow™ is a user-friendly software that allows you to create and edit robot tasks through a graphical interface using a series of function nodes, making it easy for first-time users to learn our flow-based programming without any robotics experience.

If you prefer non-graphical programming, experience a more flexible way to program by using the new Script Node and Script Project. The Script feature allows experienced engineers to program with complex logic, and freely edit robot tasks by compiling codes. Embrace the method that suits you best and enjoy coding with unparalleled freedom!




▪ Flow-based UI




▪ Script for Complex Logical Programming

### Create Personalized Interface with TMcraft for 2nd Development

TMcraft is a new architecture that allows you to create your own customized UI or background program and embed it onto TMflow™, our cobot programming software. It offers the freedom to develop third-party plug-and-play applications using C# and WPF development. Additionally, a wizard is available to facilitate the development of high-level applications, such as welding, palletizing, and sanding, making it easier to customize and create the applications you need.




▪ Developers can develop nodes in their own environment



▪ Embed into TMflow™ using third-party plugins

### Built-in vision with one-click positioning



▪ Coordinate System with TM Landmark

▪ Coordinate System on other robot

#### TM Landmark

General robot has the coordinate system built on its base, when the relative position between the objects and the robot changes, the robot require re-adjustment. With TM Landmark, the coordinate system is built on the landmark, the robot will only need to scan the landmark and the coordinate info can be updated without re-adjustment. This is especially recommended to robot with AGV!



#### Visual Calibration


TM Calibration board can largely reduce the complexity of visual calibration process. Whether users are using EIH, ETH or Upward-looking camera, just simply place the calibration board under the camera, press the button and TMvision™ will do all the work!

### Built-in vision application


#### Positioning




#### Identification



#### Measurement



#### AI Inspection



### Completely integrate hands, eyes and brain in automation field

**TM AI+™ Trainer** is a software tool that will help you manage image data, set up AI training parameters, and train AI models. The AI solution can help you train a model that fits your needs effortlessly. This AI model can be applied to both the robot arm and machine vision, thus forming a powerful combination of the arm(cobot), eye(machine vision), and brain(AI). Easy and simple UI helps the user to rapidly and conveniently introduce AI vision technology to production. AI incorporating vision system can effectively eliminate quality issues resulted from fatigue or human error.

### Features

- A graphical interface that is easy to learn
- Designed as a browser-based software that you can log in anywhere with a web browser
- All image data used for AI model training is stored in a local database to ensure enterprise classified data is secure
- Powerful AI Vision technology with capabilities including anomaly detection, classification, object detection, and semantic segmentation

### 4 steps for easy AI model training


#### Image collection



#### Collect Image Data

- Take multiple photos of the object and upload them to TM AI+™ Trainer


#### Annotation



#### TM AI+™ Trainer

- Select the type of vision task: Classification, Detection, Segmentation, Anomaly Detection
- Label the uploaded image samples
- Configure training parameters and begin training
- Evaluate the training outcome

#### Training



#### Import AI model

- Download the trained AI model from the TM AI+™ Trainer to TM Robot or external camera
- Begin AI inference


#### Deployment

### Comprehensive quality traceability for your product

After an enterprise sells its product to customers, they often must deal with customer feedback or complaints. Therefore, companies need to establish a comprehensive quality traceability system. TM Image Manager is a software tool that is highly compatible with the vision function of TM AI Cobot. It can help you effectively manage the quality inspection records of each product. The inspector can monitor the inspection progress in real time and the results are automatically recorded as image data. This data can be reviewed at any time to increase inspection accuracy. Furthermore, a quality resume can be improved and the potential cost of after-sales service activities can be reduced.

### Features


- Browser-based interface for intuitive and easy operation
- Manage inspection images and results through the database to address the needs of backup and search
- The user can filter the images of quality inspection by different conditions, like time, work order, barcode, etc. at any time
- Help inspectors to compare the images of inspection and standard item to effectively reduce the probability of misjudgement
- The user can plan and design inspection configuration to perform real-time monitoring on inspection position, result and progress



▪ Configuration inspection and progress review


▪ Backup and search of inspection history

▪ Support human double-check interface



## AI Vision Operating Architecture

The graphical interface of TM AI Cobot's integrated vision system eliminates the need for programming and enables a seamless process from image collection and annotation to training and deployment. It serves as an ideal solution for small and medium-sized enterprises (SMEs) lacking an AI or software division. Throughout production, AI Cobot accumulates valuable production history data, empowering companies to track, analyze, and integrate this information to proactively prevent defects, enhance quality, and reduce costs.



## Application Examples

### Assembly Inspection



- Checking if the tires are wrapped with PE film



- Checking if all wires are connected correctly

### Classification




- Sorting different materials for wooden furniture




- Recognition of pizza flavor and crust

### Defects Inspection




- Identifying objects with damage on the edge




- Checking if there are metal scrap on the surface

### Counting /Detection



- Counting the amount of the object in the tray



- Objects detection and 3D positioning

### Scratches /Cuts /Dents Inspection




- Checking scratches on DRAM gold fingers



- Checking the dents on metal parts

### AI OCR



- Label text reading



- Label text reading

## TM Plug&Play™ Solution

### TM certified, perfect integration, and usable upon installation

TM AI Cobot works with peripheral equipment vendors to create a comprehensive TM Plug&Play™ ecosystem. Each certified TM Plug&Play™ product has been calibrated and tested by Techman Robot and peripheral equipment vendors. This ensures users benefit from an optimal experience and highly reliable robot performance, while significantly reducing the time and labor costs associated with hardware production and automation programming.

### Start to use within 5 minutes



### Simple, efficient, and fast production line introduction

**HARDWARE PACKAGE** + **SOFTWARE PACKAGE** = **Screw Plug&Play example**

The diagram illustrates the integration of hardware and software. On the left, a green circle labeled 'HARDWARE PACKAGE' is connected by a vertical line with a plus sign to another green circle labeled 'SOFTWARE PACKAGE'. This combination leads to a central image of a TM AI Cobot arm holding a blue screwdriver. Below the robot is a screenshot of the TM software interface, showing a complex automation program with various steps and logic. A specific step in the program is highlighted with a green box and labeled 'Grip', with a sub-step labeled 'Release' below it.

### TM Plug&Play™

CERTIFIED

<b>Advantech</b> AIR-3002022-TM AI+ Trainer	<b>ARS Automation</b> FlexiBowl® Kit for TM	<b>ASPINA</b> ARH350A Kit for TM	<b>ATI</b> 9105-TM-Axia80	<b>Basler</b> Industrial Camera	<b>CKD</b> RCKL/RHLF/RLSH-TM Gripper
<b>COBOTRACKS</b> Linear Motion Plug&Play for TM	<b>DH-Robotics</b> Adaptive Gripper DH-3M Kit	<b>EWELLIX</b> LIFTKIT-TM	<b>FerRobotics</b> ACF-K Active Contact Flange-Kit	<b>Flir</b> Industrial Camera	<b>Gimatic</b> KIT-TM-J
<b>HIWIN</b> Electric Gripper X-series	<b>IDS</b> Ensenso N36/N46 3D camera	<b>Igus®</b> 3D e-chain TM Kit - PMA Tubes	<b>KILEWS</b> Screw Driver Solution	<b>Mindman</b> All-in-One Gripper for TM Robot (3-Finger)	<b>Murrplastik</b> Murrplastik FHS-SH-Set
<b>NABELL</b> Robot Flex	<b>NITTOSEIKO</b> Pick and Drive System PD400TM	<b>OnRobot</b> Sander	<b>OnRobot</b> 2FG7	<b>OnRobot</b> Screwdriver	<b>Pickit</b> Pickit3D Vision Solution
<b>RoboDK</b> Simulation and Offline Programming Software for TM	<b>Robotiq</b> FTS-300-TM-KIT	<b>Robotiq</b> Adaptive Gripper, 2-Finger 85/140 TM Kit	<b>Schmalz</b> FCXB	<b>SCHUNK</b> Changing by SCHUNK - Plug & Work Portfolio Techman Robot	<b>SCHUNK</b> Collaborative gripping EGP-C
<b>SMC</b> Magnet Gripper Unit for Collaborative Robots	<b>TOYO</b> CHY2B-S80	<b>Weiss Robotics</b> GRIPKIT-CR-PRO-L	<b>Zimmer</b> HRC-03 TM-Kit	<b>ZLÍN ROBOTICS</b> Universal Mobile Stand	More Information on <a href="http://www.tm-robot.com">www.tm-robot.com</a>

# TM AI Cobot S Series Specification



# JANATICS

Specification													
Model	TM5S	TM6S	TM7S	TM12S	TM5S-M	TM6S-M	TM7S-M	TM12S-M	TM5S-X	TM6S-X	TM7S-X	TM12S-X	
Weight	23.9kg	35.5kg	22.9kg	33.3kg	23.9kg	35.5kg	22.9kg	33.3kg	23.6kg	35.2kg	22.6kg	33kg	
Maximum Payload	5kg	6kg	7kg	12kg	5kg	6kg	7kg	12kg	5kg	6kg	7kg	12kg	
Reach	946mm	1800mm	758mm	1300mm	946mm	1800mm	758mm	1300mm	946mm	1800mm	758mm	1300mm	
Joint Ranges	J1, J2, J4, J5, J6	+/- 360°											
	J3	+/- 158°	+/- 166°	+/- 152°	+/- 162°	+/- 158°	+/- 166°	+/- 152°	+/- 162°	+/- 158°	+/- 166°	+/- 152°	+/- 162°
Speed	J1	210°/s	130°/s	210°/s	130°/s	210°/s	130°/s	210°/s	130°/s	210°/s	130°/s	210°/s	130°/s
	J2	210°/s	130°/s	210°/s	130°/s	210°/s	130°/s	210°/s	130°/s	210°/s	130°/s	210°/s	130°/s
	J3	210°/s											
	J4	225°/s											
	J5	225°/s											
	J6	450°/s											
Max. Speed	4.5m/s												
Repeatability	+/- 0.03mm	+/- 0.10mm	+/- 0.03mm	+/- 0.03mm	+/- 0.03mm	+/- 0.10mm	+/- 0.03mm	+/- 0.03mm	+/- 0.03mm	+/- 0.10mm	+/- 0.03mm	+/- 0.03mm	
Degree Of Freedom	6 rotating joints												
I/O	Control Box	Digital In: 16 / Digital Out: 16											
		Analog In: 2 / Analog Out: 2											
	Tool Conn.	Digital In: 3 / Digital Out: 3											
DO_0 (DO-0/AI) / DO_1 (DO-1/RS485-) / DO_2 (DO-2/RS485+)													
I/O Power Supply	24V 2.0A for control box, 24V 1.5A for tool												
IP Classification	IP65 (Robot Arm) <sup>*(1)</sup>				IP65 (Robot Arm) <sup>*(1)</sup>				IP65 (Robot Arm) <sup>*(1)</sup>				
	IP54 (Control Box)				IP54 (Control Box)				IP54 (Control Box)				
Typical Power Consumption	240 W	400 W	240 W	400 W	240 W	400 W	240 W	400 W	240 W	400 W	240 W	400 W	
Temperature	0~50°C												
Cleanliness	ISO Class 3												
Power Supply	100~240 VAC, 50~60 Hz				24~60 VDC				100~240 VAC, 50~60 Hz				
I/O Interface	2×COM, 1×HDMI, 3×LAN, 2×USB2.0, 4×USB3.0												
Communication	RS-232/RS-422/RS-485, Ethernet, Modbus TCP/RTU (master & slave)												
	Optionally support specified network card of PROFINET, EtherNet/IP, EtherCAT, CC-Link <sup>*(2)</sup>												
Programming Environment	TMflow (flowchart based), TMscript (script based), TMcraft (developer based)												
Certification	TÜV certificated ISO 13849-1, ISO 10218-1, ISO/TS 15066												
	SGS certificated UL1740, CAN/CSA Z424-14 (R2019)												
	CE, NSF/ANSI 169 (optional), SEMI S2 (optional)												
AI & Robot Vision													
AI Function	Classification, Object Detection, Segmentation, Anomaly Detection, AI OCR												
Application	Positioning, 1D/2D Barcode Reading, OCR, Defect Detection, Measurement, Assembly Check												
Positioning Accuracy	2D Positioning: 0.1 mm												
	TM Landmark 3D Positioning (Working Point away from Landmark 100/200/300 mm): 0.10/ 0.20/ 0.33 mm <sup>*(3)</sup>												
Eye in Hand (Built in)	Auto-focused color camera with 5M resolution, Working distance 100 mm ~ ∞												
Eye to Hand (Optional)	Support Maximum 2× GigE 2D cameras or 1× GigE 2D Camera + 1× 3D Camera <sup>*(4)</sup>												
<sup>*(1)</sup> IP65 robot arm will be available in 2025/Q3 <sup>*(2)</sup> Please contact sales/agent for detailed specifications. <sup>*(3)</sup> The data in this table are measured by TM laboratory and the working distance is 100mm. It should be noted that in practical applications, the relevant values may be different due to factors such as the on-site ambient light source, object characteristics, and vision programming methods that will affect the change in accuracy. <sup>*(4)</sup> Refer to the official website of TM Plug&Play for camera models compatible to TM Robot.													

Specification												
TM14S	TM20S	TM25S	TM30S	TM14S-M	TM20S-M	TM25S-M	TM30S-M	TM14S-X	TM20S-X	TM25S-X	TM30S-X	
33kg	33.3 kg	81.6kg	80.6kg	33kg	33.3 kg	81.6kg	80.6kg	32.7kg	33 kg	81.3kg	80.3kg	
14kg	20kg	25kg	30kg	14kg	20kg	25kg	30kg	14kg	20kg	25kg	30kg	
1100mm	1300mm	1902mm	1702mm	1100mm	1300mm	1902mm	1702mm	1100mm	1300mm	1902mm	1702mm	
+/- 360°												
+/- 159°	+/- 162°	+/- 166°	+/- 170°	+/- 159°	+/- 162°	+/- 166°	+/- 170°	+/- 159°	+/- 162°	+/- 166°	+/- 170°	
130°/s		100°/s		130°/s		100°/s		130°/s		100°/s		
130°/s	95°/s	100°/s		130°/s	95°/s	100°/s		130°/s	95°/s	100°/s		
210°/s	125°/s	130°/s		210°/s	125°/s	130°/s		210°/s	125°/s	130°/s		
225°/s	160°/s	195°/s		225°/s	160°/s	195°/s		225°/s	160°/s	195°/s		
225°/s	190°/s	210°/s		225°/s	190°/s	210°/s		225°/s	190°/s	210°/s		
450°/s		225°/s		450°/s		225°/s		450°/s		225°/s		
4.5m/s		5.2m/s		4.5m/s		5.2m/s		4.5m/s		5.2m/s		
+/- 0.03mm	+/- 0.05mm	+/- 0.05mm		+/- 0.03mm	+/- 0.05mm	+/- 0.05mm		+/- 0.03mm	+/- 0.05mm	+/- 0.05mm		
6 rotating joints												
Digital In: 16 / Digital Out: 16												
Analog In: 2 / Analog Out: 2												
Digital In: 3 / Digital Out: 3												
DO_0 (DO-0/AI) / DO_1 (DO-1/RS485-) / DO_2 (DO-2/RS485+)												
24V 2.0A for control box, 24V 1.5A for tool												
IP65 (Robot Arm) <sup>*(1)</sup>			IP65 (Robot Arm) <sup>*(1)</sup>			IP65 (Robot Arm) <sup>*(1)</sup>			IP65 (Robot Arm) <sup>*(1)</sup>			
IP54 (Control Box)			IP54 (Control Box)			IP54 (Control Box)			IP54 (Control Box)			
400 W		600 W		400 W		600 W		400 W		600 W		
0~50°C												
ISO Class 3												
100~240 VAC, 50~60 Hz	200~240 VAC, 50~60 Hz			24~60 VDC	48~60 VDC			100~240 VAC, 50~60 Hz	200~240 VAC, 50~60 Hz			
2×COM, 1×HDMI, 3×LAN, 2×USB2.0, 4×USB3.0												
RS-232/RS-422/RS-485, Ethernet, Modbus TCP/RTU (master & slave)												
Optionally support specified network card of PROFINET, EtherNet/IP, EtherCAT, CC-Link <sup>*(2)</sup>												
TMflow (flowchart based), TMscript (script based), TMcraft (developer based)												
TÜV certificated ISO 13849-1, ISO 10218-1, ISO/TS 15066												
SGS certificated UL1740, CAN/CSA Z424-14 (R2019)												
CE, NSF/ANSI 169 (optional), SEMI S2 (optional)												
AI & Robot Vision												
Classification, Object Detection, Segmentation, Anomaly Detection, AI OCR											N/A	
Positioning, 1D/2D Barcode Reading, OCR, Defect Detection, Measurement, Assembly Check												
2D Positioning: 0.1 mm												
TM Landmark 3D Positioning (Working Point away from Landmark 100/200/300 mm): 0.10/ 0.20/ 0.33 mm <sup>*(3)</sup>												
Auto-focused color camera with 5M resolution, Working distance 100 mm ~ ∞												
Support Maximum 2× GigE 2D cameras or 1× GigE 2D Camera + 1× 3D Camera <sup>*(4)</sup>												
<sup>(1)</sup> IP65 robot arm will be available in 2025/Q3 <sup>(2)</sup> Please contact sales/agent for detailed specifications. <sup>(3)</sup> The data in this table are measured by TM laboratory and the working distance is 100mm. It should be noted that in practical applications, the relevant values may be different due to factors such as the on-site ambient light source, object characteristics, and vision programming methods that will affect the change in accuracy. <sup>(4)</sup> Refer to the official website of TM Plug&Play for camera models compatible to TM Robot.												

## TM AI Cobot Specification



Specification						
Model	TM5-700	TM5-900	TM5M-700	TM5M-900	TM5X-700	TM5X-900
Weight	22.1kg	22.6kg	22.1kg	22.6kg	21.8kg	22.3kg
Maximum Payload	6kg	4kg	6kg	4kg	6kg	4kg
Reach	746mm	946mm	746mm	946mm	746mm	946mm
Joint Ranges	J1,J6	+/- 270°	+/- 270°	+/- 270°	+/- 270°	+/- 360°
	J2,J4,J5	+/- 180°	+/- 180°	+/- 180°	+/- 180°	+/- 360°
	J3	+/- 155°				
Speed	J1,J2	180°/s				
	J3	180°/s				
	J4	225°/s				
	J5	225°/s				
	J6	225°/s				
Max. Speed	4m/s					
Repeatability	+/- 0.05mm					
Degree Of Freedom	6 rotating joints					
I/O	Control Box	Digital In: 16 / Digital Out: 16 Analog In: 2 / Analog Out: 1				
	Tool Conn.	Digital In: 4 / Digital Out: 4 Analog In: 1 / Analog Out: 0				
I/O Power Supply	24V 2.0A for control box, 24V 1.5A for tool					
IP Classification	IP54 (Robot Arm) IP32 (Control Box)					
Typical Power Consumption	220 W					
Temperature	0-50°C					
Cleanliness	ISO Class 3					
Power Supply	100-240 VAC, 50-60 Hz	22-60 VDC		100-240 VAC, 50-60 Hz		
I/O Interface	3×COM, 1×HDMI, 3×LAN, 4×USB2.0, 2×USB3.0					
Communication	RS-232, Ethernet, Modbus TCP/RTU (master & slave) Optionally support specified network card of PROFINET, EtherNet/IP, EtherCAT, CC-Link <sup>*(1)</sup>					
Programming Environment	TMflow (flowchart/script based)					
Certification	ISO 13849-1, ISP 10218-1, ISO/TS 15066 CE, SEMI S2 (optional)					
AI & Robot Vision						
AI Function	Classification, Object Detection, Segmentation, Anomaly Detection, AI OCR					N/A
Application	Positioning, 1D/2D Barcode Reading, OCR, Defect Detection, Measurement, Assembly Check					
Positioning Accuracy	2D Positioning: 0.1 mm <sup>*(2)</sup>					
	TM Landmark 3D Positioning (Working Point away from Landmark 100/200/300 mm): 0.24/0.53/1.00 mm <sup>*(2)</sup>					
Eye in Hand (Built in)	Auto-focused color camera with 5M resolution, Working distance 100 mm ~ ∞					
Eye to Hand (Optional)	Support Maximum 2× GigE 2D cameras or 1× GigE 2D Camera + 1× 3D Camera <sup>*(3)</sup>					
<sup>*(1)</sup> Please contact sales/agent for detailed specifications. <sup>*(2)</sup> The data in this table are measured by TM laboratory and the working distance is 100mm. It should be noted that in practical applications, the relevant values may be different due to factors such as the on-site ambient light source, object characteristics, and vision programming methods that will affect the change in accuracy. <sup>*(3)</sup> Refer to the official website of TM Plug&Play for camera models compatible to TM Robot.						

Specification											
TM12	TM14	TM16	TM20	TM12M	TM14M	TM16M	TM20M	TM12X	TM14X	TM16X	TM20X
32.8kg	32.5kg	32kg	32.8kg	32.8kg	32.5kg	32kg	32.8kg	32.5kg	32.2kg	31.7kg	32.5kg
12kg	14kg	16kg	20kg	12kg	14kg	16kg	20kg	12kg	14kg	16kg	20kg
1300mm	1100mm	917mm	1300mm	1300mm	1100mm	917mm	1300mm	1300mm	1100mm	917mm	1300mm
+/- 270°	+/- 270°	+/- 270°	+/- 270°	+/- 270°	+/- 270°	+/- 270°	+/- 270°	+/- 360°	+/- 360°	+/- 360°	+/- 360°
+/- 180°	+/- 180°	+/- 180°	+/- 180°	+/- 180°	+/- 180°	+/- 180°	+/- 180°	+/- 360°	+/- 360°	+/- 360°	+/- 360°
+/- 166°	+/- 163°	+/- 155°	+/- 166°	+/- 166°	+/- 163°	+/- 155°	+/- 166°	+/- 166°	+/- 163°	+/- 155°	+/- 166°
120°/s	120°/s	120°/s	90°/s	120°/s	120°/s	120°/s	90°/s	120°/s	120°/s	120°/s	90°/s
180°/s	180°/s	180°/s	180°/s	180°/s	180°/s	180°/s	180°/s	180°/s	180°/s	180°/s	180°/s
180°/s	150°/s	180°/s	150°/s	180°/s	150°/s	180°/s	150°/s	180°/s	150°/s	180°/s	150°/s
180°/s	150°/s	180°/s	180°/s	180°/s	150°/s	180°/s	180°/s	180°/s	150°/s	180°/s	180°/s
180°/s	180°/s	180°/s	225°/s	180°/s	180°/s	180°/s	225°/s	180°/s	180°/s	180°/s	225°/s
4m/s											
+/- 0.1mm											
6 rotating joints											
Digital In: 16 / Digital Out: 16 Analog In: 2 / Analog Out: 1											
Digital In: 4 / Digital Out: 4 Analog In: 1 / Analog Out: 0											
24V 2.0A for control box, 24V 1.5A for tool											
IP54 (Robot Arm) IP32 (Control Box)											
300 W											
0-50°C											
ISO Class 3											
100-240 VAC, 50-60 Hz			22-60 VDC			24-60 VDC		100-240 VAC, 50-60 Hz			
3×COM, 1×HDMI, 3×LAN, 4×USB2.0, 2×USB3.0											
RS-232, Ethernet, Modbus TCP/RTU (master & slave) Optionally support specified network card of PROFINET, EtherNet/IP, EtherCAT, CC-Link <sup>*(1)</sup>											
TMflow (flowchart/script based)											
ISO 13849-1, ISP 10218-1, ISO/TS 15066 CE, SEMI S2 (optional)											
AI & Robot Vision											
Classification, Object Detection, Segmentation, Anomaly Detection, AI OCR										N/A	
Positioning, 1D/2D Barcode Reading, OCR, Defect Detection, Measurement, Assembly Check											
2D Positioning: 0.1 mm <sup>*(2)</sup>											
TM Landmark 3D Positioning (Working Point away from Landmark 100/200/300 mm): 0.24/0.53/1.00 mm <sup>*(2)</sup>											
Auto-focused color camera with 5M resolution, Working distance 100 mm ~ ∞											
Support Maximum 2× GigE 2D cameras or 1× GigE 2D Camera + 1× 3D Camera <sup>*(3)</sup>											
<sup>*(1)</sup> Please contact sales/agent for detailed specifications. <sup>*(2)</sup> The data in this table are measured by TM laboratory and the working distance is 100mm. It should be noted that in practical applications, the relevant values may be different due to factors such as the on-site ambient light source, object characteristics, and vision programming methods that will affect the change in accuracy. <sup>*(3)</sup> Refer to the official website of TM Plug&Play for camera models compatible to TM Robot.											

## Software Specification



### TM AI+ Trainer Installation Requirements

#### Software Requirements

TM AI+ Trainer Software version Ver. 2.18 or above

#### Hardware Requirements

Operating System	Ubuntu 22.04 <sup>*(1)</sup>
CPU	7th Generation Intel® Core™ i7 Processors or above
RAM	32 GB or above
Graphics Cards	Only support NVIDIA Turing and Ampere micro-architectures GPU <sup>*(2)</sup> <sup>*(3)</sup> Recommendation: NVIDIA GeForce RTX 30 series (3060 12GB or above) NVIDIA RTX professional GPUs (A4000 16GB or above)
Storage	2TB or above (SSD Recommended)
Communication Interface	Ethernet
Language Support	EN, TW, CN, DE, ES, FR, JP, KO, PT, TH, VI

- <sup>\*(1)</sup> TM AI+ Trainer cannot be installed in a virtual environment on a personal computer, such as VirtualBox.
- <sup>\*(2)</sup> Only NVIDIA GPUs are supported; GPUs from other manufacturers like AMD and Intel are not compatible.
- <sup>\*(3)</sup> NVIDIA GPUs based on other micro-architectures, such as the GeForce RTX 40 series (Ada Lovelace architecture), are also not supported.



### TM Image Manager Installation Requirements

#### Software Requirements

TMflow Software Version Ver. 2.18 or above

#### Hardware Requirements

Operating System	Ubuntu 22.04 <sup>*(1)</sup> <sup>*(2)</sup>
CPU	Gen 7 intel i7 or above
RAM	32 GB or above
Storage	SSD 2TB-8TB
Communication Interface	Ethernet
Language Support	EN, JP, KO, TH
Remark	Supports up to 10 TM AI Cobots and AI+ AOI Edges for continuous, simultaneous image transmission <sup>*(3)</sup>

- <sup>\*(1)</sup> Image Manager is not allowed to be installed on the virtual environment of personal computer, like VirtualBox.
- <sup>\*(2)</sup> Please verify if the computer hardware supports Ubuntu 22.04 LTS 64.
- <sup>\*(3)</sup> When more than 10 connections are established with simultaneous image transmissions, users should assess the potential risks of system overload.

